

AMCO LUBRICANTS FZCO.

Dubai, United Arab of Emirates
Jebel Ali Freezone, Street 531
+971 42286630



AMCO ATF III

Amco ATF is a 100% synthetic blend multipurpose transmission fluid for use in automatic gear boxes post 2005, where Dexron III is quoted. Also suitable for certain power steering systems, torque converters, change-gearboxes, fluid clutches and non-complicated hydraulic systems. sophisticated combination of high quality synthetic base oils and viscosity index improve, anti-oxidant, anti-wear, detergent, and friction modifying additives.

Benefits

- Smooth transmission and perfect synchronization
- Longer retention of frictional characteristics under continual severe operating conditions
- Protection against deposit formation and evaporation losses at high operating temperatures
- Excellent low temperature operation, ensuring prompt circulation of fluid
- Good protection, against wear, resistance to rust, corrosion and foam
- Compatible with seal materials used in transmission units
- Lower maintenance costs, and improved operating profit

Performance Levels

Meets and exceeds:

GM DEXRON III H,

Ford Mercon, Allison C-4

Application

Used in automatic transmissions and manual transmissions, in torque converters and numerous power steering systems in accordance with the specifications of the manufacturer.

Product Characteristics

Properties	Units	Value	Test Method
Specific Gravity @ 15 °C	g/cc	.841	ASTM D4052
Viscosity @40°C	mm ² /s	31.35	ASTM D445
Viscosity @100°C	mm ² /s	6.8	ASTM D445
Viscosity Index	–	185	ASTM D2270
Flash Point, COC	°C	208	ASTM D92
Foam ml,max	MI	0/0/0	ASTM D892
Pour Point	°C	-48	ASTM D2896

*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.

