



# AMCO VELOX TITANIUM 5W40 API SP

AMCO VELOX Titanium 5W40 API SP is the flagship engine oil for AMCO Lubricants. Formulated using unique premium synthetic base oil and technologically advanced additive system to provide exceptional thermal and oxidation stability for optimum performance and extended drain interval in very hot and extremely cold severe driving conditions. Expertly Engineered to combine durability and protection with low-viscosity, low friction motor oil.

## Benefits

- Low viscosity and low friction for fuel economy
- High film strength at extremes of temperature
- Excellent fluidity during cold starting, giving instant wear protection.
- Exceptional thermal stability ensuring adequate protection at extreme temperature operations.
- Low emissions ensure adequate protection of emission control devices fitted on modern cars.
- Exceptional deposit control, ensuring the protection of engine surfaces and piston rings.
- Exceptional sludge control

## Performance Levels

Meets and Exceeds the requirements of  
API SP, SN+, SN RC, SN  
ILSAC GF-6A  
GM Dexos 1

## Application

Recommended for most types of petrol engines and light diesel engines fitted with the latest emission control devices, including those with turbochargers. It caters for the demanding lubrication requirements of engines operating under all conditions, including extreme temperature conditions.

## Product characteristics

Properties	Units	Value	Test Method
Specific Gravity @ 15 °C	g/cc	0.85	ASTM-4052
Viscosity @40°C	mm <sup>2</sup> /s	76.1	ASTM D-445
Viscosity @100°C	mm <sup>2</sup> /s	13.4	ASTM D-445
Viscosity Index	-	170	ASTM D-2270
Flash Point, COC	°C	208	ASTM D-92
Pour Point	°C	-39	ASTM D-2896
TBN	Mg KOH/g	8.2	ASTM D-892

\*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.