



AMCO VELOX PLATINIUM 5W40

AMCO VELOX PLATINIUM is a semi synthetic lubricant formulated with high quality base oils combined with advanced additive technology to meet high performance requirements of the latest model car and trucks. It has been expertly engineered to help deliver superior cleaning power, wear protection and outstanding performance. It helps resist degradation between oil changes, extending the time and mileage interval between oil changes. Advanced polymer technology provides optimum viscosity and fluidity across a broad range of temperatures.

Benefits

Improved oxidation stability, leading to lower deposit formation and cleaner engines.

Advanced additive package neutralizes corrosive particles.

Improved wear protection, leading to longer engine life.

Optimum fuel economy

Low volatility, leading to lower oil consumption.

Applications

Formulated to operate in almost all types of conditions. It is recommended for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline and diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and light trucks.

Performance Levels

Meets and Exceeds:

- API SN, SN/CF
- ACEA A3/B3
- MB 229.3
- VW 502 00, VW 505 00

Product characteristics

Properties	Units	Value	Test Method
Specific Gravity @ 15 °C	g/cc	0.851	ASTM-4052
Viscosity @40°C	mm ² /s	87.8	ASTM D-445
Viscosity @100°C	mm ² /s	14.52	ASTM D-445
Viscosity Index	-	173	ASTM D-2270
Flash Point, COC	°C	212	ASTM D-92
Pour Point	°C	-39	ASTM D-2896
TBN	Mg KOH/g	8.2	ASTM D-892

*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.